

Premium Wash Care Resin Ribbon

BARCODING THE WORLD

TDR382 is a premium wash care ribbon with high sensitivity and







(ਨੂੰ) Excellent Washing & Sand Washing Resistance

Printing Quality

Darkness



1.60 ODR

Sharpness



0° barcode



90° barcode



Min. printable character



Graphics



Substrate Compatibility

L3- 0 < L2- 0 < L1- 0 Nylon TDR370P TDR380P TDR382

Sensitivity

Printing speed



Printing temperature Medium

Resistance Test

Washing resistance

Placing the printed label in a washing machine with 4‰ soapy water at 40°C for 30 minutes.

Observing its print attenuation: OK



No Obvious Fading

Dry-cleaning resistance

Placing the printed label in a washing machine with CCL4 solution at 40°C for 30 minutes.

Observing its print attenuation: OK



No Obvious Fading

Ironing test

Placing the printed label under an ironing machine for 5 minutes. Observing its print attenuation: OK



No Obvious Fading

Recommended Applications



Receipt and delivery labels for warehouses




Pre-packaging

Digital & electronics

Nursery gardens

Fixed assets

Garment labels



Refrigeration



Logistics



Clothing tags

م اللله

BAR CODE BAR CODE

Production lines

Electrical

equipment

Shoe tongues



Hot working

Pharmaceuticals

Labels for automobile industry



Wooden products





Mechanical equipment



Chemical industry

Daily chemicals

Retail label


Steel & iron manufacturing



Properties

| PET film | Ribbon |
|--|----------------------|
| Thickness: 4.5μm | Thickness: 6.0±1.0μm |
| Ink | |
| Color: black Melting point: 115±3°C | |
| Storage condition | |
| Temperature: 5~35°C Humidity: 20~80% Validity period: 12 months | |

Product Comparison



Certifications and Permits



ROHS2.0



REACH



ISO9001/14001



MSDS



HALOGEN

Premium Wash Care Resin Ribbon

BARCODING THE WORLD



Hangzhou Todaytec Digital Co., Ltd.

All product specifications can be found at our website www.todaytec.com/en/



(Marketing Department: +86 571-8577-1623



marketing@todaytec.com.cn

